

INTEGRATED TRIBAL DEVELOPMENT AGENCY: BARIPADA

ସମନ୍ୱିତ ଆଦିବାସୀ ଉନ୍ନୟନ ସଂସ୍ଥା : ବାରିପଦା

(Ph. & Fax No. (06792) 260250, email- itdabpd@nic.in&itdabpd@gmail.com)

SHORT QUOTATION CALL NOTICE

No. 3332 /IXB-61/24 ITDA, Dt. 23-09-2025

Sealed quotations are invited in plain paper by the Project Administrator, ITDA, Baripada from desirous registered firms/suppliers/ authorized registered dealers for supply of the following articles to the office of the P.A. ITDA, Baripada They must have valid PAN & GST etc. along with quotation documents. The bidder should submit their bid document in sealed cover in person or by Registered post only. The last date of receipt of sealed bids as on 03-10-2025 during office hours up to 5:30 P.M. The sealed bid shall be opened by the Project Administrator, ITDA, Baripada in presence of the committee and bidders or in the presence of their authorized representative in the office chamber of the Project Administrator, ITDA, Baripada on 04-10-2025 at 11:00 A.M. (The details of items can be had from the office of the Project Administrator, ITDA, Baripada in person.

Sl. No.	Description of items	Quantity	Size	Amount
1	Supply, fitting and fixing of Dhauli Shanti Stupa made up of FRP	1 No.	Height-29 Feet Width-21 Feet	
2	Supply of fitting and fixing of statue of the following freedom fighter / eminent personalities made up of FRP 1 Pandit Gapabandhu Das 2 Pandit Raghunath Murmu 3 Freedom Fighter Dharanidhar Bhuyan 4 Freedom Fighter Bhagaban Birsha Munda	1 No. 1 No. 1 No. 1 No.	Height of the all statue -9 Feet	

The specification of the above statue should be as follows.

Supply, fitting and fixing of Dhauli Shanti Stupa made up of FRP with general specifications as mention below :

- Materials :
Resin: Vinyl ester / Epoxy based
Fibers: chopped strand mat CMS (300–450 g/m²) + woven roving or stitched biaxial (450–600 g/m²) oriented longitudinally / circumferentially.
- Dimensions : Key computed geometry & area - Height: 8.839 m. Diameter: 6.401 m, with Hemisphere surface area 64.35 m², Drum lateral area 49.03 m², Plinth lateral area 64.35 m², Total exposed FRP surface area 178 m².
- Thickness & Reinforcement: Laminate thickness: 5 mm to 15 mm (based on pressure, size, and load). Reinforcement: extra layers at joints, flanges, and supports and load locations. Overall shell thickness: 5–15 mm typical (thickness varied by area). Outer finish: UV-stable pigmented gelcoat 0.4–0.8mm. Barrier coat: 0.3–0.8 mm for moisture resistance
- Operating Conditions: Temperature resistance: 0°C to 65°C .
- Accessories / Fittings : Manholes, agitator supports, ladders, handrails, anchors and frame.
- Finish: Internal: smooth anti-corrosive barrier coat. External : UV-resistant gel coat/top coat. Surface prep for painting: etch primer compatible with FRP if painting over gelcoat. Colouring: pigmented gel coat for long-term colour fastness.
- Drainage, access & maintenance : small drain holes and/or routed drains for any hollow pockets to prevent water accumulation. Provide one inspection/man-access hatch (locked) to allow internal inspection of anchors and frame.

Supply, fitting and fixing of statue of freedom fighter / eminent personalities made up of FRP with general specifications as mention below :

- Technical specification — FRP statue, height 2.74 m
- Typical overall footprint / base: base plate 600–900 mm or rectangular pad as required.
- Estimated exposed surface area (statue shell): 4.5–7.0 m² (depends on pose/bulk).
- Construction: hollow FRP shell with internal structural reinforcement/armature.
- Materials : Resin -Isophthalic polyester & epoxy based for chemical/water resistance.
Fibers: chopped strand mat CMS (300–450 g/m²) + woven roving or stitched biaxial (450–600 g/m²) oriented longitudinally/circumferentially. Directional roving (unidirectional or biaxial) at areas needing high stiffness/strength (limbs, neck, attachment points).
- Internal armature/frame: mild steel or galvanized mild steel with isolating coating (if metal-to-resin contact).
- Finish : Internal: smooth anti-corrosive barrier coat. External : UV-resistant gel coat/top coat. Surface prep for painting: etch primer compatible with FRP if painting over gelcoat. Coloring: pigmented gelcoat for long-term color fastness.
- Mechanical properties : Density: 1.6–1.9 g/cm³, Tensile strength (laminate): 80–150 MPa
- Estimated weight range: 90 kg to 120 kg.
Drainage: include small drain holes in hollow sections where water could collect (avoid corrosion traps on embedded metal).


Terms and conditions

1. The supply Organization /firm /agency must have valid GST number.
2. The Organization /firm/agency must have valid PAN in the name of the Organization.
3. The Organization /firm/ agency must have not black listed by any state / Central Govt. agency/ Organization.
4. The organization /firm /agency must mentioned price of the article Including the expenditure towards transportation & installation (specified separately) at the point.
5. The quote price must be clearly mentioned in the bid separately cost & GST.
6. There shouldn't be any overwriting/correction in the tender page.
7. Decision of the selection committee is final & can't be alleged at any circumstances.
8. The undersigned reserved all the rights to cancel any or all quotation without assigning any reason.


Project Administrator, 23/09/2025
ITDA, Baripada.

Memo No. 3332 /IXB-61/24 ITDA, Dt. 23.9.2025

Copy to Notice Board of I.T.D.A, Baripada/ /District Welfare Officer, Mayurbhanj
/CDO-cum-EO Zilla Parishad, Mayurbhanj/ Addl. District Magistrate, Mayurbhanj
District Planning Officer, Mayurbhanj Baripada for wide publication.


Project Administrator, 23/09/2025
ITDA, Baripada.